

2S Clamp Set

(B 05 33)

effortless installation: push into drill hole and twist 15 - 127 mm



Features and benefits

- two-screw clamp
- gapless range
- anti-loss washers prevent screws from falling out during installation
- material: clamp and hanger bolt made of steel; plug made of PA (polyamide)
- zinc plated

Part No.	D (mm)	D (°)	DN	G	B (mm)	H (mm)	h (mm)	b x s (mm)	F _{a,z} (N)	Pack 1
33215019	15 - 19	3/8	10	M8	51	32	20	20 x 1.00	700	50
33215024	20 - 24	1/2	15	M8	56	37	22	20 x 1.00	700	50
33215030	25 - 30	3/4	20	M8	62	43	25	20 x 1.00	700	50
33215037	31 - 37	1	25	M8	69	50	29	20 x 1.00	700	50
33215046	38 - 46	1 1/4	32	M8	78	60	34	20 x 1.25	950	50
33215052	47 - 52	1 1/2	40	M8	84	66	37	20 x 1.25	950	50
33215061	53 - 61	2	50	M8	93	75	41	20 x 1.25	950	50
33215067	62 - 67	-	-	M8	99	81	44	20 x 1.25	950	50
33215081	75 - 81	2 1/2	65	M8/10	118	103	60	20 x 1.50	1,400	50
33215095	88 - 95	3	80	M8/10	136	119	68	23 x 2.00	2,000	50
33215112	104 - 112	-	-	M8/10	153	136	76	23 x 2.00	2,000	25
33215118	113 - 118	4	100	M8/10	159	142	79	23 x 2.00	2,000	25
33215127	119 - 127	-	-	M8/10	168	151	84	23 x 2.00	2,000	25

≤DN80 Hanger bolt M8x80; plug ø10x50.
 >DN80 Hanger bolt M10x80; plug ø12x60.

