

2S Clamp Set with EPDM Lining

(A 05 158)

effortless installation: push into drill hole and twist 10 - 225 mm



Features and benefits

- two-screw clamp
- gapless range
- anti-loss washers prevent screws from falling out during installation
- material: clamp and hanger bolt made of steel; plug made of PA (polyamide)
- zinc plated
- noise insulating lining, EPDM rubber, black

Part No.	D (mm)	D (°)	DN	G	B (mm)	H (mm)	h (mm)	b x s (mm)	F _{a,z} (N)	Pack 1
33245014	10 - 14	1/8 - 1/4	6 - 8	M8	51	32	20	20 x 1.00	330	50
33245019	15 - 19	3/8	10	M8	56	37	22	20 x 1.00	330	50
33245024	20 - 24	1/2	15	M8	62	43	25	20 x 1.00	330	50
33245030	25 - 30	3/4	20	M8	69	50	29	20 x 1.00	330	50
33245037	31 - 37	1	25	M8	75	56	32	20 x 1.00	330	50
33245046	38 - 46	1 1/4	32	M8	84	66	37	20 x 1.25	500	50
33245052	47 - 52	1 1/2	40	M8	93	75	41	20 x 1.25	500	50
33245061	53 - 61	2	50	M8	99	81	44	20 x 1.25	500	50
33245067	62 - 67	-	-	M8	106	87	47	20 x 1.25	500	50
33245081	75 - 81	2 1/2	65	M8/10	124	109	63	20 x 1.50	850	50
33245095	88 - 95	3	80	M8/10	143	127	72	23 x 2.00	1,000	50
33245112	104 - 112	-	-	M8/10	159	142	79	23 x 2.00	1,000	25
33245118	113 - 118	4	100	M8/10	168	151	84	23 x 2.00	1,000	25
33245127	119 - 127	-	-	M8/10	178	161	89	23 x 2.00	1,000	25
33245137	128 - 137	-	-	M8/10	185	168	92	23 x 2.00	1,000	25
33245144	138 - 144	5	125	M8/10	194	177	97	23 x 2.00	1,000	25
33245162	154 - 162	-	-	M8/10	211	194	105	23 x 2.00	1,000	25
33245172	163 - 172	6	150	M8/10	227	210	114	25 x 2.50	2,350	15
33245205	195 - 205	-	-	M8/10	260	243	130	25 x 2.50	2,350	10
33245225	217 - 225	8	200	M8/10	279	261	140	25 x 2.50	2,350	10

≤DN80 Hanger bolt M8x80; plug ø10x50.

>DN80 Hanger bolt M10x80; plug ø12x60.

