


Pacifyre® A Acrylic Fire Sealant

(U 04 100)



Features and benefits

- up to EI 240 for linear gap seals
 - up to EI 120 for pipe penetration
 - up to EI 90 for cable penetration
 - single insulated metal pipes up to DN200
 - multiple insulated metal pipes up to DN80
 - cable bundles up to Ø 50 mm (max. Ø 21 mm each cable)
 - for sealing annular joints around pipes, fire collars and fire sleeves or wraps
 - remains elastic after curing
 - colour fast, waterproof and paintable after curing
 - shrinkage approx. 15% (DIN 52451)
 - indoor emission level A+
 - temperature resistance from -20 °C to +80 °C
 - application temperature: +5 °C up to +30 °C
 - sound reduction up to 62dB
 - pipe and cable penetrations: CE marked ETA 22/0037
 - linear gap seals: CE marked ETA 16/1008
 - tested according to EN 1366-3, EN 1366-4 and EN ISO 717-1
- for more information, please refer to the Declaration of Performance / ETA, www.walraven.com/pacifyre



Part No.	Colour	Certification	Cont.	Pack 1
2180100010	White	ETA	300 ml	12

Complementary

Pacifyre® MK II Fire Sleeve (P)
 Pacifyre® EFC Fire Collar
 Pacifyre® BFC

Complementary

Pacifyre® ID-Card
 WIS Dispenser Gun