

WNP Nail Plug

(L 07 18)

easy to install hammer-set anchor



Features and benefits

- quick and easy to install
- pre-assembled
- long expansion zone provides stability
- can be adjusted or dismantled
- material: steel
- material: high quality PA6 polyamide
- zinc plated
- substrate type:
 - concrete
 - masonry
 - rock
 - stone
 - sand-lime bricks
 - natural stone

Part No.	Code	L	d _s	d ₀	h ₀	l _s	h _{nom,mi} n	t _{fix,max}	Drive	Rec. Tension Load Solid Brick (kN)	Pack 1	Pack 2
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)				
62232604	WNP 6x40	40 mm	4	6	40	40	30	10	PZ2	0,20	200	2.400
62232606	WNP 6x60	60 mm	4	6	40	60	30	20	PZ2	0,20	200	2.400
62232806	WNP 8x60	60 mm	4	8	50	60	40	20	PZ2	0,45	100	-
62232808	WNP 8x80	80 mm	4	8	50	80	40	40	PZ2	0,45	100	-
62232810	WNP 8x100	100 mm	4	8	50	100	40	60	PZ2	0,45	100	-

Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 2.

