## walraven

(H 19 25)

## Walraven Wall Mounting Set 62 H + Support

universal Mounting Set for outdoor appliances



## Features and benefits

- suitable for indoor and outdoor use
- universal mounting brackets for fixing indoor and outdoor appliances to the wall
- designed for the most common standard surface treatment: hot dip galvanized heat pumps (for heat pump models with female thread, Walraven Wall Mounting set consists of: ISO Kit 6901998 needs to be ordered separately - see assembly instruction)
- stepless adjustable in height and wall distance
- with anti-vibration mounts type Walraven VibraTek<sup>®</sup> SB-MM

- material: steel 1.0332
- material: vibration damper; rubber SBR +
  - NR 55°+-5 Shore A steel class 4.8
- (EN-ISO 1461)
- - 2 Cantilever Arms type RapidStrut 62 H with welded support
  - 2 lengths of 500mm wall rail type RapidStrut 62|H
  - 4 vibration dampers with preassembled fasteners
  - 6 rail endcaps
  - fasteners to connect Cantilever Arms to the wall rail
  - assembly instruction
  - anchors for mounting to the wall not included (order seperately)

Part No.	Туре	L	<b>L1</b> (mm)	<b>H</b> (mm)	<b>h</b> (mm)	F <sub>a,z</sub> (N)	Pack 1	Арр.
6901990	62   H + Support	970 mm	900	808	400	1.750	1	pc.
Max. allowed load $F_{a,z}$ per Set: 1.750 Newton (Total weight of the unit).								

