


Walraven Yeti® 335 Step-Over with 4 Steps


(I 10 20)


prefabbed Step-Over Set for Rooftop Installations




Features and benefits

- complete set for installation of Step-Over on flat and low pitched roofs
- with non-slip anti-vibration mat
- predefined load capacity: calculation not necessary
- pre-assembled ready-to-use set for quick installation
- with hand railing made from non-perforated rail
- mouldings made of WPC, a composite of recycled plastic and wood fibre
- resistant to UV and chemical influences
- rail system construction: surface protection:
- product is part of the BIS UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- grids / steps: surface protection: hot dip galvanized
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3 up to 31 dB(A)
- UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
- designs according to EN 14122

  
Nr.  
1762-001-19

  
ITB No.  
LZM00-02259



Part No.	L	L1 (mm)	B (mm)	B1 (mm)	H (mm)	H1 (mm)	H2 (mm)	F <sub>a,z</sub> (N)	Pack 1
67685833	3,733 mm	1.771 mm	1,362	1,000	2,008	806	880	2,000	1

For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.  
In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation.

