## walraven

## starQuick® Duo Wall Plate

accessories BIS starQuick® Pipe Clamps without Nut

(C0520)





## Features and benefits

- for fixing of two pipes with starQuick<sup>®</sup>
  Clamps
- suitable for starQuick® Clamps up to SO-20
- the distance between the pipe and the wall is equal to that of a single clip
- material: modified PA6 (polyamide), grey or white
- resistant to UV, ageing, oil and petrol
- no corrosion, recyclable, halogen free
- temperature resistance from approx. -40 °C to approx. +90 °C (constant); short to approx. +130 °C

| Part No.   | Model | L     | В    | d1       | k    | Colour           | $F_{a,z}$ | Pack 1 | Pack 2 |
|--|-------|-------|------|----------|------|------------------|-----------|--------|--------|
|  |       |       | (mm) | (mm)     | (mm) |                  | (N)       |        |        |
| 0854000  | -     | 20 mm | 75   | 4.8 x 10 | 50   | Grey (RAL 7035)  | 600       | 100    | 1,200  |
| 0855000  | -     | 20 mm | 75   | 4.8 x 10 | 50   | White (RAL 9003) | 600       | 100    | 1,200  |
| 0854300  |       | 20 mm | 75   | 4.8 x 10 | 50   | Grey (RAL 7035)  | 600       | 50     | 600    |
|  | screw |       |      |          |      |                  |           |        |        |
| Hammer-in screw: suitable for fixing into concrete, aerated concrete, brick. |       |       |      |          |      |                  |           |        |        |

