

# Walraven Ursus Foot Support System (BUP1000)

(1 04 20)

for Rooftop Installations



## Features and benefits

- for supporting small pipework systems, ductwork runs and cable trays
- to support climate installations, walkways on flat roofs, etc.
- does not penetrate the waterproof membrane (at PVC roofs a separating layer must be installed to protect against plasticizer migration - see Walraven BIS Yeti® Triplex Separation Layer)
- material: vulcanized rubber, black; Strut Rail made of steel
- UV resistant
- Strut Rail: surface protection:
  - product is part of the BIS UltraProtect® 1000 system
  - suitable for in and outdoor applications
  - stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227



Part No.	Model	L	L	B	B	H	H	h	h	F <sub>a,z</sub>	F <sub>a,z</sub>	Pack 1
			(")	(mm)	(")	(mm)	(")	(mm)	(")	(N)	(lbf)	
67687250	Horizontal, including rail	250 mm	10	130	5.11	50	2.0	80	3.15	1,000	225	1
67687400	Horizontal, including rail	400 mm	16	130	5.11	50	2.0	80	3.15	2,000	450	1
67687601	Horizontal, including rail	600 mm	24	200	7.87	50	2.0	80	3.15	3,000	675	1

For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.

In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation.

