

Rubber Lined Split Clamp

(A 05 184)

15 - 318 mm



Features and benefits

- lock bolts with combi cross recessed head
- for horizontal and vertical applications
- profiled for extra strength
- screws secured with anti-loss washer
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- temperature resistance from -20 °C to +110 °C
- noise insulating lining, rubber, black
- noise reduction up to 18dB (A)

| Part No. | D (mm) | D (°) | DN | G | B (mm) | H (mm) | h (mm) | b x s (mm) | F _{a,z} (N) | Pack 1 |
|-----------|-----------|----------|-----|-------|-----------|-----------|-----------|---------------|-------------------------|--------|
| DMC215018 | 15 - 19 | 3/8 | 15 | M8 | 60 | 36 | 26 | 19 x 1.2 | 1,500 | 450 |
| DMC215022 | 20 - 25 | 1/2 | 22 | M8 | 65 | 43 | 29 | 19 x 1.2 | 1,500 | 400 |
| DMC215028 | 36 - 30 | 3/4 | 28 | M8 | 70 | 50 | 32 | 19 x 1.2 | 1,500 | 350 |
| DMC215035 | 32 - 36 | 1 | 35 | M8 | 85 | 56 | 36 | 19 x 1.2 | 1,500 | 300 |
| DMC215040 | 38 - 43 | 1 1/4 | 42 | M8 | 92 | 63 | 39 | 19 x 1.2 | 1,500 | 250 |
| DMC215048 | 47 - 51 | 1 1/2 | 48 | M8 | 98 | 72 | 42 | 19 x 1.2 | 1,500 | 200 |
| DMC215054 | 53 - 58 | - | 54 | M8 | 104 | 75 | 45 | 19 x 1.2 | 1,500 | 200 |
| DMC215060 | 60 - 64 | 2 | 60 | M8 | 110 | 81 | 48 | 19 x 1.2 | 1,500 | 125 |
| DMC215063 | 36 - 66 | - | 63 | M8 | 115 | 88 | 51 | 19 x 1.2 | 1,500 | 125 |
| DMC215070 | 68 - 72 | - | 70 | M8 | 120 | 91 | 53 | 19 x 1.2 | 1,500 | 125 |
| DMC215075 | 74 - 80 | 2 1/2 | 75 | M8/10 | 125 | 96 | 56 | 19 x 1.5 | 2,000 | 100 |
| DMC215083 | 81 - 86 | - | 83 | M8/10 | 139 | 108 | 60 | 19 x 1.5 | 2,000 | 100 |
| DMC215090 | 87 - 92 | 3 | 90 | M8/10 | 146 | 111 | 63 | 19 x 1.5 | 2,000 | 100 |
| DMC215100 | 99 - 105 | 3 1/2 | 100 | M8/10 | 156 | 121 | 68 | 19 x 1.5 | 2,000 | 75 |
| DMC215110 | 107 - 112 | - | 110 | M8/10 | 166 | 131 | 73 | 19 x 1.5 | 2,000 | 75 |
| DMC215115 | 113 - 118 | 4 | 115 | M8/10 | 171 | 136 | 76 | 19 x 1.5 | 2,000 | 70 |
| DMC215125 | 125 - 130 | - | 125 | M8/10 | 181 | 146 | 81 | 19 x 2.0 | 2,000 | 70 |
| DMC215133 | 131 - 137 | - | 133 | M8/10 | 184 | 154 | 85 | 19 x 2.0 | 2,000 | 50 |
| DMC215140 | 138 - 142 | 5 | 140 | M8/10 | 196 | 161 | 88 | 19 x 2.0 | 2,000 | 50 |
| DMC215150 | 148 - 153 | - | 150 | M8/10 | 206 | 171 | 93 | 19 x 2.0 | 2,000 | 50 |
| DMC215160 | 159 - 166 | - | 160 | M8/10 | 216 | 181 | 98 | 19 x 2.0 | 2,000 | 50 |
| DMC215168 | 168 - 172 | 6 | 168 | M8/10 | 224 | 189 | 102 | 19 x 2.0 | 2,000 | 50 |
| DMC215200 | 200 - 212 | - | 200 | M8/10 | 256 | 221 | 118 | 19 x 2.0 | 3,000 | 50 |
| DMC215220 | 215 - 220 | 8 | 220 | M8/10 | 276 | 241 | 128 | 19 x 2.0 | 3,000 | 40 |
| DMC215250 | 249 | - | 250 | M8/10 | 306 | 271 | 143 | 19 x 2.0 | 3,000 | 40 |
| DMC215315 | 313 - 318 | - | 315 | M8/10 | 371 | 336 | 176 | 19 x 2.0 | 3,000 | 25 |

Hot Dip Galvanized and Stainless Steel option available on request.
 With connection nut M8/M10, M10/M12 available on request.
 With M6 Side Nuts available on request.
 These series replaces part number DMC115 series.

