

Rubber Lined U-Strap Clamp

(A 14 305)

22 - 230 mm



Features and benefits

- for mounting plain or insulated pipes
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- temperature resistance from -20 °C to +110 °C
- noise insulating lining, rubber, black
- noise reduction up to 18dB (A)
- designed to meet MSS Standard SP-58, type 26 and SP-69

Part No.	D (mm)	D (")	Bolt	B (mm)	b x s (mm)	k (mm)	F _{a,z} (N)	Pack 1
DMC188022	22	1/2	M8	79	25 x 2.0	54	5,500	500
DMC188028	28	3/4	M8	85	25 x 2.0	60	5,500	400
DMC188035	35	1	M8	92	25 x 2.0	67	5,500	400
DMC188040	42	1 1/4	M8	99	25 x 2.0	74	5,500	350
DMC188048	48	1 1/2	M8	105	25 x 2.0	80	5,500	300
DMC188054	54	-	M8	111	25 x 2.0	86	5,500	250
DMC188060	62	2	M8	117	25 x 2.0	92	5,500	200
DMC188067	67	-	M8	124	25 x 2.0	99	5,500	200
DMC188075	75	2 1/2	M8	148	25 x 3.0	116	6,500	150
DMC188082	82	-	M8	155	25 x 3.0	123	6,500	150
DMC188090	90	3	M8	163	25 x 3.0	131	6,500	150
DMC188100	100	3 1/2	M8	173	25 x 3.0	141	6,500	150
DMC188108	108	-	M8	181	25 x 3.0	149	6,500	125
DMC188115	115	4	M8	188	25 x 3.0	156	6,500	125
DMC188126	126	-	M10	199	25 x 3.0	167	6,500	125
DMC188140	140	5	M10	213	25 x 3.0	181	6,500	100
DMC188148	148	-	M10	221	25 x 3.0	189	6,500	100
DMC188155	155	-	M10	228	25 x 3.0	196	6,500	100
DMC188168	168	6	M10	240	25 x 3.0	208	6,500	100
DMC188179	179	-	M10	252	25 x 3.0	220	6,500	100
DMC188190	190	-	M10	263	38 x 3.0	231	9,000	50
DMC188205	205	-	M10	278	38 x 3.0	246	9,000	50
DMC188219	219	8	M10	292	38 x 3.0	260	9,000	50
DMC188230	230	-	M10	303	38 x 3.0	271	9,000	30

Other dimensions on request.

Hot Dip Galvanized and Stainless Steel option available on request.

