

# Rubber Lined U-Strap Clamp

(A 14 310)

241 - 918 mm



## Features and benefits

- for mounting plain or insulated pipes
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- temperature resistance from -20 °C to +110 °C
- noise insulating lining, rubber, black
- noise reduction up to 18dB (A)
- designed to meet MSS Standard SP-58, type 26 and SP-69

Part No.	D (mm)	D (°)	Bolt	B (mm)	b x s (mm)	k (mm)	F <sub>az</sub> (N)	Pack 1
DMC188241	241	-	M12	335	38 x 4.0	294	13,500	35
DMC188263	263	-	M12	357	38 x 4.0	316	13,500	35
DMC188273	273	10	M18	367	38 x 4.0	326	13,500	35
DMC188295	295	-	M18	389	38 x 4.0	348	13,500	30
DMC188323	323	12	M18	417	38 x 4.0	376	13,500	30
DMC188356	356	14	M18	450	50 x 4.0	409	19,000	10
DMC188374	374	-	M18	468	50 x 4.0	427	19,000	15
DMC188406	406	16	M18	500	50 x 4.0	459	19,000	15
DMC188432	432	-	M18	526	50 x 4.0	485	19,000	15
DMC188456	456	18	M18	550	50 x 4.0	509	19,000	10
DMC188482	482	-	M18	576	50 x 4.0	535	19,000	10
DMC188508	508	20	M18	602	50 x 4.0	561	19,000	10
DMC188533	533	-	M18	627	50 x 4.0	586	19,000	10
DMC188559	559	-	M18	653	50 x 4.0	612	19,000	10
DMC188583	583	-	M18	677	50 x 4.0	636	19,000	10
DMC188610	610	24	M18	704	60 x 4.0	663	19,000	10
DMC188658	658	-	M18	769	50 x 6.0	721	24,000	5
DMC188690	690	-	M18	801	50 x 6.0	753	24,000	5
DMC188760	760	-	M18	870	50 x 6.0	823	24,000	5
DMC188863	863	-	M18	974	50 x 6.0	926	24,000	5
DMC188918	918	-	M18	1,029	50 x 6.0	981	24,000	5

Other dimensions on request.

Hot Dip Galvanized and Stainless Steel option available on request.

