

# Rubber Support Insert – 13 mm

(D 15 305)

0.0 - 219.1 mm



## Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
  - 1/2" to 2": 25 mm
  - 2" to 5": 38 mm
  - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 - 1,400 kg/m<sup>3</sup>
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI121325	21.3	1/2	15	22	25	Steel + Copper pipe	600
DMRSI341325	26.7	3/4	20	28	25	Steel + Copper pipe	500
DMRSI11325	33.4	1	25	35	25	Steel + Copper pipe	400
DMRSI1141325	42.1	1 1/4	32	42	25	Steel + Copper pipe	350
DMRSI1121325	48.2	1 1/2	40	-	-	Steel Pipe	300
DMRSI21325	60.3	2	50	-	-	Steel Pipe	250
DMRSI2121338	73.0	2 1/2	65	76	37	Steel + Copper pipe	200
DMRSI31338	88.9	3	80	-	-	Steel Pipe	100
DMRSI3121338	101.6	3 1/2	90	-	-	Steel Pipe	80
DMRSI41338	114.3	4	100	-	-	Steel Pipe	80
DMRSI51338	141.3	5	125	-	-	Steel Pipe	80
DMRSI61350	168.3	6	150	-	-	Steel Pipe	50
DMRSI81350	219.1	8	200	-	-	Steel Pipe	30
DMRSI161325	0.0	-	-	16	25	Copper Pipe	600
DMRSI1141225	0.0	-	-	42	25	Copper Pipe	600
DMRSI541325	0.0	-	6	54	25	Copper Pipe	600
DMRSI671325	0.0	-	-	67	25	Copper Pipe	600
DMRSI1081338	0.0	-	-	108	38	Copper Pipe	600
DMRSI1331338	0.0	-	-	133	38	Copper Pipe	600
DMRSI1601350	0.0	-	-	160	50	Copper Pipe	600

Self extinguishing rubber inserts available on request.