

Rubber Support Insert – 19 mm

(D 15 310)

0.0 - 219.1 mm



Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
 - 1/2" to 2": 25 mm
 - 2" to 5": 38 mm
 - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 - 1,400 kg/m³
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI121925	21.3	1/2	15	22	25	Steel + Copper pipe	400
DMRSI341925	26.7	3/4	20	28	25	Steel + Copper pipe	350
DMRSI11925	33.4	1	25	35	25	Steel + Copper pipe	300
DMRSI1141925	42.1	1 1/4	32	42	25	Steel + Copper pipe	250
DMRSI1121925	48.2	1 1/2	40	-	-	Steel + Copper pipe	200
DMRSI21925	60.3	2	50	22	25	Steel + Copper pipe	175
DMRSI2121938	73.0	2 1/2	65	76	38	Steel + Copper pipe	100
DMRSI31938	88.9	3	80	-	-	Steel Pipe	80
DMRSI3121938	101.6	3 1/2	90	-	-	Steel Pipe	80
DMRSI41938	114.3	4	100	-	-	Steel Pipe	60
DMRSI51938	141.3	5	125	-	-	Steel Pipe	50
DMRSI61950	168.3	6	150	-	-	Steel Pipe	35
DMRSI81950	219.1	8	200	-	-	Steel Pipe	20
DMRSI161925	0.0	-	-	16	25	Copper Pipe	400
DMRSI541925	0.0	-	-	54	25	Copper Pipe	400
DMRSI671925	0.0	-	-	67	25	Copper Pipe	400
DMRSI1081938	0.0	-	-	108	38	Copper Pipe	400
DMRSI1331938	0.0	-	-	133	38	Copper Pipe	400
DMRSI1601950	0.0	-	-	160	50	Copper Pipe	400

Self extinguishing rubber inserts available on request.