

Rubber Support Insert – 19 mm

(D 15 310)

0.0 - 219.1 mm



Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
 - 1/2" to 2": 25 mm
 - 2" to 5": 38 mm
 - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 - 1,400 kg/m³
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

| Part No. | D (mm) | D (") | DN | d (mm) | B (mm) | For | Pack 1 |
|--------------|-----------|----------|-----|-----------|-----------|---------------------|--------|
| DMRSI121925 | 21.3 | 1/2 | 15 | 22 | 25 | Steel + Copper pipe | 400 |
| DMRSI341925 | 26.7 | 3/4 | 20 | 28 | 25 | Steel + Copper pipe | 350 |
| DMRSI11925 | 33.4 | 1 | 25 | 35 | 25 | Steel + Copper pipe | 300 |
| DMRSI1141925 | 42.1 | 1 1/4 | 32 | 42 | 25 | Steel + Copper pipe | 250 |
| DMRSI1121925 | 48.2 | 1 1/2 | 40 | - | - | Steel + Copper pipe | 200 |
| DMRSI21925 | 60.3 | 2 | 50 | 22 | 25 | Steel + Copper pipe | 175 |
| DMRSI2121938 | 73.0 | 2 1/2 | 65 | 76 | 38 | Steel + Copper pipe | 100 |
| DMRSI31938 | 88.9 | 3 | 80 | - | - | Steel Pipe | 80 |
| DMRSI3121938 | 101.6 | 3 1/2 | 90 | - | - | Steel Pipe | 80 |
| DMRSI41938 | 114.3 | 4 | 100 | - | - | Steel Pipe | 60 |
| DMRSI51938 | 141.3 | 5 | 125 | - | - | Steel Pipe | 50 |
| DMRSI61950 | 168.3 | 6 | 150 | - | - | Steel Pipe | 35 |
| DMRSI81950 | 219.1 | 8 | 200 | - | - | Steel Pipe | 20 |
| DMRSI161925 | 0.0 | - | - | 16 | 25 | Copper Pipe | 400 |
| DMRSI541925 | 0.0 | - | - | 54 | 25 | Copper Pipe | 400 |
| DMRSI671925 | 0.0 | - | - | 67 | 25 | Copper Pipe | 400 |
| DMRSI1081938 | 0.0 | - | - | 108 | 38 | Copper Pipe | 400 |
| DMRSI1331938 | 0.0 | - | - | 133 | 38 | Copper Pipe | 400 |
| DMRSI1601950 | 0.0 | - | - | 160 | 50 | Copper Pipe | 400 |

Self extinguishing rubber inserts available on request.