

# Rubber Support Insert – 25 mm

(D 15 315)

0.0 – 406.4 mm



## Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
  - 1/2" to 2": 25 mm
  - 2" to 5": 38 mm
  - 6" and above: 50 mm
  - non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 – 1,400 kg/m<sup>3</sup>
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI122525	21.3	1/2	15	22	25	Steel + Copper pipe	250
DMRSI342525	26.7	3/4	20	28	25	Steel + Copper pipe	250
DM RSI1 2 525	33.4	1	25	35	25	Steel + Copper pipe	200
DMRSI1142525	42.1	1 1/4	32	42	25	Steel + Copper pipe	175
DMRSI1122525	48.2	1 1/2	40	-	-	Steel Pipe	150
DM RSI2 2 525	60.3	2	50	-	-	Steel Pipe	125
DMRSI2122538	73.0	2 1/2	65	76	38	Steel + Copper pipe	70
DM RSI3 2 538	88.9	3	80	-	-	Steel Pipe	60
DMRSI3122538	101.6	3 1/2	90	-	-	Steel Pipe	55
DM RSI4 2 538	114.3	4	100	-	-	Steel Pipe	50
DM RSI5 2 538	141.3	5	125	-	-	Steel Pipe	40
DM RSI6 2 550	168.3	6	150	-	-	Steel Pipe	25
DM RSI8 2 550	219.1	8	200	-	-	Steel Pipe	20
DMRSI102550	273.0	10	250	-	-	Steel Pipe	12
DMRSI122550	323.8	12	300	-	-	Steel Pipe	10
DMRSI142550	355.6	14	350	-	-	Steel Pipe	7
DMRSI162550	406.4	16	400	-	-	Steel Pipe	100
DMRSI542525	0.0	-	-	54	25	Copper Pipe	200
DMRSI672525	0.0	-	-	67	25	Copper Pipe	200
DMRSI1082538	0.0	-	-	108	38	Copper Pipe	200
DMRSI1332538	0.0	-	-	133	38	Copper Pipe	200
DMRSI1602550	0.0	-	-	160	50	Copper Pipe	200

Self extinguishing rubber inserts available on request.