

Rubber Support Insert – 32 mm

(D 15 320)

0.0 – 609.6 mm



Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
 - 1/2" to 2": 25 mm
 - 2" to 5": 38 mm
 - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 – 1,400 kg/m³
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI123225	21.3	1/2	15	22	25	Steel + Copper pipe	150
DMRSI343225	26.7	3/4	20	28	25	Steel + Copper pipe	125
DMRSI13225	33.4	1	25	35	25	Steel + Copper pipe	125
DMRSI1143225	42.1	1 1/4	32	42	25	Steel + Copper pipe	125
DMRSI1123225	48.2	1 1/2	40	-	-	Steel Pipe	100
DMRSI23225	60.3	2	50	22	25	Steel + Copper pipe	90
DMRSI2123238	73.0	2 1/2	65	76	38	Steel + Copper pipe	50
DMRSI33238	88.9	3	80	-	-	Steel Pipe	50
DMRSI3123238	101.6	3 1/2	90	-	-	Steel Pipe	40
DMRSI43238	114.3	4	100	-	-	Steel Pipe	40
DMRSI53238	141.3	5	125	-	-	Steel Pipe	30
DMRSI63250	168.3	6	150	-	-	Steel Pipe	20
DMRSI83250	219.1	8	200	-	-	Steel Pipe	15
DMRSI103250	273.0	10	250	-	-	Steel Pipe	10
DMRSI123250	323.8	12	300	-	-	Steel Pipe	7
DMRSI143250	355.6	14	350	-	-	Steel Pipe	7
DMRSI163250	406.4	16	400	-	-	Steel Pipe	100
DMRSI183250	457.2	18	150	-	-	Steel Pipe	60
DMRSI203250	508.0	20	500	-	-	Steel Pipe	50
DMRSI243250	609.6	24	600	-	-	Steel Pipe	40
DMRSI163225	0.0	-	-	16	25	Copper Pipe	125
DMRSI543225	0.0	-	-	54	25	Copper Pipe	125
DMRSI673225	0.0	-	-	67	25	Copper Pipe	125
DMRSI1083238	0.0	-	-	108	38	Copper Pipe	125
DMRSI1333238	0.0	-	-	133	38	Copper Pipe	125
DMRSI1603250	0.0	-	-	160	50	Copper Pipe	125

Self extinguishing rubber inserts available on request.