

# Rubber Support Insert – 50 mm

(D 15 330)

0.0 – 609.6 mm



## Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
  - 1/2" to 2": 25 mm
  - 2" to 5": 38 mm
  - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 – 1,400 kg/m<sup>3</sup>
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

| Part No.     | D<br>(mm) | D<br>(") | DN  | d<br>(mm) | B<br>(mm) | For                 | Pack 1 |
|--------------|-----------|----------|-----|-----------|-----------|---------------------|--------|
| DMRSI125025  | 21.3      | 1/2      | 15  | 22        | 25        | Steel + Copper pipe | 80     |
| DMRSI345025  | 26.7      | 3/4      | 20  | 28        | 25        | Steel + Copper pipe | 70     |
| DMRSI15025   | 33.4      | 1        | 25  | 35        | 25        | Steel + Copper pipe | 70     |
| DMRSI1145025 | 42.1      | 1 1/4    | 32  | -         | -         | Steel Pipe          | 60     |
| DMRSI1125025 | 48.2      | 1 1/2    | 40  | -         | -         | Steel Pipe          | 60     |
| DMRSI25025   | 60.3      | 2        | 50  | -         | -         | Steel Pipe          | 50     |
| DMRSI2125038 | 73.0      | 2 1/2    | 65  | 76        | 38        | Steel + Copper pipe | 30     |
| DMRSI35038   | 88.9      | 3        | 80  | -         | -         | Steel Pipe          | 30     |
| DMRSI3125038 | 101.6     | 3 1/2    | 90  | -         | -         | Steel Pipe          | 80     |
| DMRSI45038   | 114.3     | 4        | 100 | 42        | 25        | Steel + Copper pipe | 25     |
| DMRSI550358  | 141.3     | 5        | 125 | -         | -         | Steel Pipe          | 20     |
| DMRSI65050   | 168.3     | 6        | 150 | -         | -         | Steel Pipe          | 15     |
| DMRSI85050   | 219.1     | 8        | 200 | -         | -         | Steel Pipe          | 10     |
| DMRSI105050  | 273.0     | 10       | 250 | -         | -         | Steel Pipe          | 8      |
| DMRSI125050  | 353.8     | 12       | 300 | -         | -         | Steel Pipe          | 100    |
| DMRSI145050  | 355.6     | 14       | 350 | -         | -         | Steel Pipe          | 100    |
| DMRSI165050  | 406.4     | 16       | 400 | -         | -         | Steel Pipe          | 70     |
| DMRSI185050  | 457.2     | 18       | 450 | -         | -         | Steel Pipe          | 50     |
| DMRSI205050  | 508.0     | 20       | 500 | -         | -         | Steel Pipe          | 40     |
| DMRSI245050  | 609.6     | 24       | 600 | -         | -         | Steel Pipe          | 30     |
| DMRSI165025  | 0.0       | -        | -   | 16        | 25        | Copper Pipe         | 50     |
| DMRSI545025  | 0.0       | -        | -   | 54        | 25        | Copper Pipe         | 50     |
| DMRSI675025  | 0.0       | -        | -   | 67        | 25        | Copper Pipe         | 50     |
| DMRSI1085038 | 0.0       | -        | -   | 108       | 38        | Copper Pipe         | 50     |
| DMRSI1335038 | 0.0       | -        | -   | 133       | 38        | Copper Pipe         | 50     |
| DMRSI1605050 | 0.0       | -        | -   | 160       | 50        | Copper Pipe         | 50     |

*Self extinguishing rubber inserts available on request.*