

# Rubber Support Insert – 50 mm

(D 15 330)

0.0 – 609.6 mm



## Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
  - 1/2" to 2": 25 mm
  - 2" to 5": 38 mm
  - 6" and above: 50 mm
- non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 – 1,400 kg/m<sup>3</sup>
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

Part No.	D (mm)	D (")	DN	d (mm)	B (mm)	For	Pack 1
DMRSI125025	21.3	1/2	15	22	25	Steel + Copper pipe	80
DMRSI345025	26.7	3/4	20	28	25	Steel + Copper pipe	70
DMRSI15025	33.4	1	25	35	25	Steel + Copper pipe	70
DMRSI1145025	42.1	1 1/4	32	-	-	Steel Pipe	60
DMRSI1125025	48.2	1 1/2	40	-	-	Steel Pipe	60
DMRSI25025	60.3	2	50	-	-	Steel Pipe	50
DMRSI2125038	73.0	2 1/2	65	76	38	Steel + Copper pipe	30
DMRSI35038	88.9	3	80	-	-	Steel Pipe	30
DMRSI3125038	101.6	3 1/2	90	-	-	Steel Pipe	80
DMRSI45038	114.3	4	100	42	25	Steel + Copper pipe	25
DMRSI550358	141.3	5	125	-	-	Steel Pipe	20
DMRSI65050	168.3	6	150	-	-	Steel Pipe	15
DMRSI85050	219.1	8	200	-	-	Steel Pipe	10
DMRSI105050	273.0	10	250	-	-	Steel Pipe	8
DMRSI125050	353.8	12	300	-	-	Steel Pipe	100
DMRSI145050	355.6	14	350	-	-	Steel Pipe	100
DMRSI165050	406.4	16	400	-	-	Steel Pipe	70
DMRSI185050	457.2	18	450	-	-	Steel Pipe	50
DMRSI205050	508.0	20	500	-	-	Steel Pipe	40
DMRSI245050	609.6	24	600	-	-	Steel Pipe	30
DMRSI165025	0.0	-	-	16	25	Copper Pipe	50
DMRSI545025	0.0	-	-	54	25	Copper Pipe	50
DMRSI675025	0.0	-	-	67	25	Copper Pipe	50
DMRSI1085038	0.0	-	-	108	38	Copper Pipe	50
DMRSI1335038	0.0	-	-	133	38	Copper Pipe	50
DMRSI1605050	0.0	-	-	160	50	Copper Pipe	50

*Self extinguishing rubber inserts available on request.*