

Rubber Support Insert – 65 mm

(D 15 335)

21.3 - 609.6 mm



Features and benefits

- used at the supporting points of insulated pipes to prevent crushing of insulation
- inherently superior to wood
- very high load bearing capacity
- dimensionally accurate as each piece is moulded
- tongue and groove design
- available with steel reinforcements for higher sizes
- standard width:
 - 1/2" to 2": 25 mm
 - 2" to 5": 38 mm
 - 6" and above: 50 mm
 - non standard widths also available
- excellent resistance to deterioration / distortion
- density: 1,100 - 1,400 kg/m³
- thermal conductivity: 0.16 w/m °C
- temperature resistance from -20 °C to +110 °C
- designed to meet BS3974-1 : 1974

| Part No. | D (mm) | D (") | DN | d (mm) | B (mm) | For | Pack 1 |
|--------------|-----------|----------|-----|-----------|-----------|------------|--------|
| DMRSI126525 | 21.3 | 1/2 | 15 | - | - | Steel Pipe | 50 |
| DMRSI346525 | 26.7 | 3/4 | 20 | - | - | Steel Pipe | 50 |
| DMRSI16525 | 33.4 | 1 | 25 | - | - | Steel Pipe | 35 |
| DMRSI1146525 | 42.1 | 1 1/4 | 32 | - | - | Steel Pipe | 35 |
| DMRSI1126525 | 48.2 | 1 1/2 | 40 | - | - | Steel Pipe | 30 |
| DMRSI26525 | 60.3 | 2 | 50 | - | - | Steel Pipe | 25 |
| DMRSI2126538 | 73.0 | 2 1/2 | 65 | - | - | Steel Pipe | 20 |
| DMRSI36538 | 88.9 | 3 | 80 | - | - | Steel Pipe | 20 |
| DMRSI3126538 | 101.6 | 3 1/2 | 90 | - | - | Steel Pipe | 15 |
| DMRSI46538 | 114.3 | 4 | 100 | - | - | Steel Pipe | 15 |
| DMRSI56538 | 141.3 | 5 | 125 | - | - | Steel Pipe | 12 |
| DMRSI66550 | 168.3 | 6 | 150 | - | - | Steel Pipe | 10 |
| DMRSI86550 | 219.1 | 8 | 200 | - | - | Steel Pipe | 100 |
| DMRSI106550 | 273.0 | 10 | 250 | - | - | Steel Pipe | 80 |
| DMRSI126550 | 323.8 | 12 | 300 | - | - | Steel Pipe | 70 |
| DMRSI146550 | 355.6 | 14 | 350 | - | - | Steel Pipe | 80 |
| DMRSI166550 | 406.4 | 16 | 400 | - | - | Steel Pipe | 60 |
| DMRSI186550 | 457.2 | 18 | 450 | - | - | Steel Pipe | 40 |
| DMRSI206550 | 508.0 | 20 | 500 | - | - | Steel Pipe | 30 |
| DMRSI246550 | 609.6 | 24 | 600 | - | - | Steel Pipe | 20 |

Self extinguishing rubber inserts available on request.