

# U Bolt

21 - 610 mm

(B 14 305)



## Features and benefits

- high load capacity due to one piece design
- supplied with two or four nuts
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- designed to meet MSS Standard SP-58, type 26 and SP-69
- special U bolts with longer tangents and threads available on request

Part No.	D (mm)	D (")	G	H (mm)	Lm1 (mm)	F <sub>a,z</sub> (N)	Pack 1
DMC144022	21	1/2	M10	65	50	6,000	250
DMC144028	27	3/4	M10	77	50	6,000	200
DMC144035	34	1	M10	85	50	6,000	200
DMC144042	43	1 1/4	M10	93	50	6,000	175
DMC144048	48	1 1/2	M10	100	50	6,000	150
DMC144060	60	2	M10	110	50	6,000	150
DMC144075	76	2 1/2	M12	127	50	10,000	100
DMC144090	89	3	M12	140	50	10,000	75
DMC144115	115	4	M12	165	50	10,000	75
DMC144140	140	5	M12	190	50	10,000	70
DMC144168	168	6	M12	220	50	10,000	50
DMC144219	219	8	M16	295	75	20,000	20
DMC144273	273	10	M20	370	100	32,500	10
DMC144324	324	12	M20	420	100	32,500	10
DMC144356	356	14	M20	455	100	32,500	10
DMC144406	406	16	M20	505	100	32,500	10
DMC144457	457	18	M24	555	100	45,000	5
DMC144508	508	20	M24	605	100	45,000	5
DMC144610	610	24	M24	710	100	45,000	5

Hot Dip Galvanized option available on request.  
Alternate rod sizes for different pipe sizes available on request.

