

# BIS Mengerling® Sealing Ring

for pipe DN 50 - DN 200

(N 20 05)



## Features and benefits

- easy to install (without lubricant)
- for use up to 0.5 bar internal pressure
- for connecting and sealing of cast iron pipe with socket with SML or HT/PE-pipe
- material: EPDM rubber, black
- tested according to DIN 4060

Part No.	DN	Model	Type	Pack 1
7300050	50	GA-collar to SML or GA-Pipe	I	100
7300070	70	GA-collar to SML or GA-Pipe	I	100
7300100	100	GA-collar to SML or GA-Pipe	I	250
7300125	125	GA-collar to SML or GA-Pipe	I	20
7300150	150	GA-collar to SML or GA-Pipe	I	20
7300200	200	GA-collar to SML or GA-Pipe	I	10
7301050	50	GA-collar to SML or GA-Pipe	A	100
7301070	70	GA-collar to SML or GA-Pipe	A	100
7301100	100	GA-collar to SML or GA-Pipe	A	250
7301125	125	GA-collar to SML or GA-Pipe	A	20
7301150	150	GA-collar to SML or GA-Pipe	A	20
7301200	200	GA-collar to SML or GA-Pipe	A	10
7302050	50	GA-collar to HT/PE-Pipe	IS	100
7302125	125	GA-collar to HT/PE-Pipe	IS	20
7303050	50	GA-collar to HT/PE-Pipe	AS	100
7303070	70	GA-collar to HT/PE-Pipe	AS	100
7303125	125	GA-collar to HT/PE-Pipe	AS	20

*Sealing Rings for HT-tube (Part No. 730XXXX) DN 40 up to DN 200 on stock.*