

BIS RapidRail® Connector 135°

(G 35 10)

to make BIS RapidRail® fabrications



Features and benefits





- connector with pre-assembled BIS RapidRail® Slide nut(s)
- to make rail fabrications
- suitable for rail 27x18, 30x15, 30x20, 30x30, 30x45, 38x40
- with pre-assembled BIS RapidRail® Sliding nut(s) for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated



RAL-GZ 655/D
Cert.Nr. 2012-09

Part No.	Model	a (°)	T _(inst.) (Nm)	For Rail	F _{a,z} (N)	F _{a,x} (N)	RAL	Pack 1
6584053	Short / short	135°	15.0	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	1,336	448	RAL ¹	25
6584051	Long / long	135°	15.0	27x18, 30x15, 30x20, 30x30, 30x45, 38x40	1,562	1,109	RAL ¹	25

*RAL¹ = tested, certified and monitored by a third party according to RAL-GZ 655/D in combination with Rail 30x15, 30x30, 30x20 and 30x45.
For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.*



Complementary

Walraven RapidRail® Fixing Rail