

BISOFIX® E13 + Bifix® G2

(D 03 06)

for insulated pipes 8.0 - 168.3 mm



Features and Benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density <80mm = 80kg/m³
- PIR density >80mm = 120kg/m³
- PIR density 80kg/m³ => 0,024-0,026 [W/m²*K]
- PIR density 120kg/m³ => 0,030-0,032 [W/m²*K]
- surface protection:
 - product is part of the BIS UltraProtect® 1000 system
 - suitable for in- and outdoor applications
 - stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

| Part No. | Consists Of | D (mm) | Model | F _{a,z} (N) | Pack 1 |
|------------|----------------------|---------------|--------------------------------|-------------------------|--------|
| I133008008 | I130000008 + 3008039 | 8.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008010 | I130000010 + 3008039 | 10.2 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008012 | I130000012 + 3008039 | 12.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008015 | I130000015 + 3008045 | 15.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008018 | I130000018 + 3008045 | 17.2 - 18.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008022 | I130000022 + 3008052 | 21.3 - 22.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008028 | I130000028 + 3008058 | 26.9 - 28.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008035 | I130000035 + 3008064 | 33.7 - 35.0 | BISOFIX® E13 + Bifix® G2 Clamp | 100 | 50 |
| I133008042 | I130000042 + 3008070 | 42.4 | BISOFIX® E13 + Bifix® G2 Clamp | 150 | 50 |
| I133008048 | I130000048 + 3008079 | 48.3 | BISOFIX® E13 + Bifix® G2 Clamp | 225 | 50 |
| I133008054 | I130000054 + 3008083 | 54.0 | BISOFIX® E13 + Bifix® G2 Clamp | 225 | 50 |
| I133008057 | I130000057 + 3008083 | 57.0 | BISOFIX® E13 + Bifix® G2 Clamp | 350 | 50 |
| I133008060 | I130000060 + 3008091 | 60.3 | BISOFIX® E13 + Bifix® G2 Clamp | 350 | 50 |
| I133008064 | I130000064 + 3008105 | 64.0 | BISOFIX® E13 + Bifix® G2 Clamp | 350 | 50 |
| I133008070 | I130000070 + 3008105 | 70.0 | BISOFIX® E13 + Bifix® G2 Clamp | 425 | 50 |
| I133008076 | I130000076 + 3008115 | 76.1 | BISOFIX® E13 + Bifix® G2 Clamp | 575 | 25 |
| I133008089 | I130000089 + 3008130 | 88.9 | BISOFIX® E13 + Bifix® G2 Clamp | 875 | 25 |
| I133008102 | I130000102 + 3008140 | 101.6 | BISOFIX® E13 + Bifix® G2 Clamp | 1,000 | 25 |
| I133008108 | I130000108 + 3008140 | 108.0 | BISOFIX® E13 + Bifix® G2 Clamp | 1,075 | 25 |
| I133008114 | I130000114 + 3008160 | 114.3 | BISOFIX® E13 + Bifix® G2 Clamp | 1,250 | 25 |
| I133008133 | I130000133 + 3008169 | 133.0 | BISOFIX® E13 + Bifix® G2 Clamp | 1,475 | 25 |
| I133008140 | I130000140 + 3008180 | 139.7 | BISOFIX® E13 + Bifix® G2 Clamp | 1,700 | 5 |
| I133008160 | I130000160 + 3008200 | 159.0 - 160.0 | BISOFIX® E13 + Bifix® G2 Clamp | 1,950 | 5 |
| I133008168 | I130000168 + 3008200 | 168.3 | BISOFIX® E13 + Bifix® G2 Clamp | 2,125 | 5 |