

Tangit FP 550 2C Fire Protection Foam

(U 08 05)

sealing of penetrations



Features and Benefits

- for fire-proof and smoke-proof sealing of partitions for pipes, cables and combinations
- also for light partition walls greater than 10 cm thick
- fire-proof and gas-tight for at least 90 minutes
- reliable and automatic filler for a wide variety of partitions
- user friendly for instructed first time users
- discard the initial material (about 3 strokes) until the components are being thoroughly mixed
- the cartridge can be closed again once the opening has been cleaned
- always apply with Tangit 2C Pistol PP6
- Instruction required before applied. Please contact your sales representative for instruction options.
- excellent and economical foam yield (approx. 3.5 litres)
- aging resistant
- rapid hardening: can be cut after approx. 4 minutes; fully hardened after approx. 20 minutes
- tested according to EN 1366-3
- compliant with DIN 4102 and MLAR 2005/LAR/RbALei
- flame-retardant as per DIN 4102 (B1)
- replacement mixing tubes are available (Tangit FP 504 Spare Mixer Pack)
- for further information please refer to our other technical documents



Part No.	Colour	Cont.	Pack 1
2181550	Pink	300 ml	6

Complementary

Pacifyre® MK II Fire Sleeve (P)
Tangit FP 800 Fire Protection Coating
Tangit FP 504 Spare Mixer Pack

Complementary

Tangit 2C Pistol PP6
Pacifyre® ID-Card