walraven

Walraven RapidRail® Stainless Steel Fixing Rail

(M 20 05)

suspension and support

6507001 6507015 6507002

Features and Benefits

- C-profile
- for a quick and easy fixing
- with continuous perforation
- distance between rail end and first hole is always equal
- a continuous graduated centimetre scale on one side
- material: stainless steel 1.4404 (AISI 316L)

RAL-GZ 655/C
Cert.Nr. 2012-07

Part No.	Type	L	B (mm)	H (mm)	s (mm)	S (mm)	RAL	BndS	BndL
6507001	30x15	2 m	30	15	2.00	15	-	20	480
6507015	30x20	2 m	30	20	1.75	15	-	20	480
6507002	30x30	2 m	30	30	2.00	15	RAL[1]	20	400

RAL[1] = tested, certified and monitored by a third party according to RAL-GZ 655/C.
For detailed technical information about our RAL marked products, please see the RAL datasheet in our web catalogue.
For more information about the max. allowed load ($F_{a,z}$) please refer to the loading tables or our online datasheet 'Technical Details BIS RapidRail®'.



WM1

Complementary

Walraven RapidRail® Stainless Steel Slide Nut
Walraven RapidRail® Stainless Steel Hammerfix

EN-INT 10/2024- Subject to modifications