

# Walraven WDI2R Drop-in Anchor

(L 03 21)

reduced length drop-in anchor with a lip collar



## Features and Benefits

- increased productivity – the reduced 25mm anchor length minimizes drilling depth and speeds up installation
- approved applications in precast prestressed hollow core slabs
- material: steel
- zinc plated
- fire resistance class R30-R120 for design of anchorages under exposure to fire
- European Technical Assessment according to EAD 330747-00-0601 (May 2018) for fasteners for use in concrete for redundant non-structural systems
- complies with VdS CEA 4001: 2024-01 (08) for applications with sprinkler systems in concrete elements
- substrate type:
  - cracked concrete
  - non-cracked concrete
- for loads and more information, refer to the product data sheet and/or the ETA report



Part No.	Size	L	B (mm)	H (mm)	d <sub>0</sub> (mm)	h <sub>0</sub> (mm)	h <sub>min</sub> (mm)	h <sub>nom</sub> (mm)	T <sub>(inst.)</sub> (Nm)	Pack 1
6103310825	M8	11	11	25	10	≥ 28	80	≥ 25	11.0	100
6103311025	M10	13	13	25	12	≥ 28	80	≥ 25	17.0	50
6103311225	M12	16	16	25	15	≥ 29	80	≥ 25	38.0	50

