

BIS Mengering® Rapid

for pipe DN 40 - DN 200

(N 05 20)



Features and benefits

- single screw connector
- defined locking torque without using a special tool
- tested for fire safety applications
- axial tensile strength up to 0.5 bar DN 40 - DN 200
- easy and fast to install due to visual torque control
- material:
 - collar: chrome steel 1.4510/11 (AISI 430 Ti)
 - locking unit: steel 1.4301 / 1.4510/11 (AISI 430 Ti)
 - bolts / nuts: steel, plated
 - sealing ring: EPDM, black



| Part No. | D (mm) | DN | Bolt | B (mm) | b (mm) | T _(max.) (Nm) | CE | Pack 1 |
|----------|-----------|-----|------|-----------|-----------|-----------------------------|----|--------|
| 7454050 | 70 | 50 | M8 | 80 | 40 | Tight-locking | CE | 100 |
| 7454070 | 90 | 70 | M8 | 100 | 40 | Tight-locking | CE | 100 |
| 7454080 | 95 | 80 | M8 | 105 | 40 | Tight-locking | CE | 100 |
| 7454100 | 125 | 100 | M8 | 135 | 46 | Tight-locking | CE | 100 |
| 7454125 | 147 | 125 | M8 | 162 | 55 | Tight-locking | CE | 70 |
| 7454150 | 172 | 150 | M8 | 187 | 55 | Tight-locking | CE | 50 |
| 7454200 | 227 | 200 | M10 | 244 | 70 | Tight-locking | CE | 15 |

Please note! BIS Mengering® Rapid is alternative for BIS Mengering® CV.

