

# WIS Chemical Anchor WVSF200


(L 03 90)

high performance chemical anchoring system for cracked concrete and rebar connections



## Features and benefits

- reduced edge and anchor spacing distances
  - always correct mixing ratio thanks to the static mixer nozzle
  - approved for use with rebars as anchors in non-cracked concrete
  - cartridge may be used up over several times (each installation after a break requires new mixing nozzle)
  - ETA Option 1 approval for cracked and non-cracked concrete
  - A+ VOC emissions class
  - ETA TRO23 for post-installed rebar connections
  - seismic performance category C1 for design of anchorages under seismic action
  - tested according to LEED 2009 EQ c4.1, SCAQMD rule 1168 (2005)
  - WRAS Material Approval for contact with potable water
- substrate type:
    - cracked concrete
    - non-cracked concrete



Part No.	Code	ETA	LEED	WRAS	VOC+	Seismic	Cont.	Pack 1
6099123E	WVSF200	ETA	LEED	WRAS	VOC+	C1	300 ml	12
6099125E	WVSF200	ETA	LEED	WRAS	VOC+	C1	410 ml	12

*For more information, please refer to the ETA report.*

### Complementary

- WIS Extension Pipe
- WIS Brush
- WIS Blow Pump

### Complementary

- WIS Dispenser Gun
- WIS Plastic Mesh Sleeve
- WIS Threaded Rod