

WNP Nail Plug

(L 07 15)

easy to install hammer-set anchor



Features and benefits

- quick and easy to install
- pre-assembled
- through-fixing
- long expansion zone provides stability
- can be adjusted or dismantled
- Application:
 - skirtings
 - cable clamps
 - profiles
 - cabinets
- material: steel
- material: high quality PA6 polyamide
- zinc plated
- substrate type:
 - concrete
 - masonry
 - hollow masonry
 - rock
 - sand-lime bricks
 - natural stone

Part No.	Code	L	d ₀	h ₀	h _{nom,m} in	t _{fix,max}	Drive	Rec. Tension Load Solid Brick	Rec. Tension Load C20/25 Concrete	Rec. Tension Load Sandstone	Pack 1	Pack 2
			(mm)	(mm)	(mm)	(mm)		(kN)	(kN)	(kN)		
62230604	WNP 6x40	40 mm	6	50	30	10	PZ2	0.25	0.30	0.20	100	1,800
62230606	WNP 6x60	60 mm	6	70	30	30	PZ2	0.25	0.30	0.20	100	1,200
62230806	WNP 8x60	60 mm	8	70	40	20	PZ2	0.30	0.40	0.25	100	900
62230808	WNP 8x80	80 mm	8	90	40	40	PZ2	0.30	0.40	0.25	100	600
62230810	WNP 8x100	100 mm	8	110	40	60	PZ2	0.30	0.40	0.25	100	600

Given recommended loads include a safety factor of 5.

