

BISOFIX® E13 + HD500

(D 03 08)

for insulated pipes 76.1 - 168.3 mm



Features and Benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 80\text{mm} = 120\text{kg/m}^3$
- surface protection:
 - product is part of the Walraven BIS UltraProtect® 1000 system
 - suitable for in- and outdoor applications
 - stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Part No.	Consists Of	D (mm)	Model	F _{a,z} (N)	Pack 1
I133304076	I130000076 + 33048116	76.1	BISOFIX® E13 + HD500 Clamp	575	25
I133304089	I130000089 + 33048133	88.9	BISOFIX® E13 + HD500 Clamp	875	25
I133304102	I130000102 + 33048140	101.6	BISOFIX® E13 + HD500 Clamp	1,000	25
I133304108	I130000108 + 33048140	108.0	BISOFIX® E13 + HD500 Clamp	1,075	25
I133304114	I130000114 + 33048154	114.3	BISOFIX® E13 + HD500 Clamp	1,250	15
I133304133	I130000133 + 33048169	133.0	BISOFIX® E13 + HD500 Clamp	1,475	15
I133304140	I130000140 + 33048183	139.7	BISOFIX® E13 + HD500 Clamp	1,700	5
I133304160	I130000160 + 33048202	159.0 - 160.0	BISOFIX® E13 + HD500 Clamp	1,950	5
I133304168	I130000168 + 33048202	168.3	BISOFIX® E13 + HD500 Clamp	2,125	5