

# Clevis Hanger

(B 22 310)



## Features and Benefits

- designed for chilled water pipe work and fire fighting systems
- design permits vertical adjustment of pipe after installation
- hanger load nut above clevis must be tightened securely to ensure proper hanger performance
- material: steel
- electrogalvanized as per ASTM B 633 Standards (SC3)
- designed to meet MSS Standard SP-58, type 1 and SP-69



Part No.	D (")	Bolt	H (mm)	b (mm)	s (mm)	s1 (mm)	d1 (mm)	F <sub>a,z</sub> (N)	FM	UL	Pack 1
WMC122022	1/2	M8 x 60 mm	70	25	3.0	3.0	10	4,000	FM	UL	125 *
WMC122028	3/4	M8 x 68 mm	76	25	3.0	3.0	10	4,000	FM	UL	125 *
WMC122035	1	M8 x 78 mm	82	25	3.0	3.0	10	4,000	FM	UL	125 *
WMC122040	1 1/4	M8 x 82 mm	92	25	3.0	3.0	10	4,000	FM	UL	125 *
WMC122048	1 1/2	M8 x 88 mm	100	25	3.0	3.0	10	4,000	FM	UL	100 *
WMC122060	2	M10 x 110 mm	117	25	3.0	3.0	10	4,000	FM	UL	75 *
WMC122075	2 1/2	M10 x 125 mm	146	25	4.0	4.0	10	6,500	FM	UL	60 *
WMC122090	3	M10 x 140 mm	155	25	4.0	4.0	10	6,500	FM	UL	50 *
WMC122100	3 1/2	M10 x 155 mm	173	25	4.0	4.0	10	6,500	FM	UL	40 *
WMC122115	4	M10 x 170 mm	198	32	6.0	6.0	10	8,000	FM	UL	20 *
WMC122140	5	M12 x 195 mm	232	32	6.0	6.0	12	8,000	FM	UL	15 *
WMC122168	6	M12 x 225 mm	266	40	5.0	6.0	12	11,000	FM	UL	10 *
WMC122219	8	M12 x 275 mm	338	40	5.0	6.0	12	11,000	FM	UL	15 *
WMC122273	10	M16 x 360 mm	419	40	6.0	6.0	16	160,100	-	-	10
WMC122323	12	M20 x 420 mm	490	50	6.0	10.0	20	169,000	-	-	6
WMC122355	14	M20 x 455 mm	556	50	6.0	10.0	20	186,800	-	-	6
WMC122406	16	M24 x 510 mm	610	65	6.0	12.0	24	204,600	-	-	3
WMC122457	18	M24 x 555 mm	675	65	6.0	12.0	24	213,500	-	-	3
WMC122508	20	M24 x 610 mm	715	75	10.0	12.0	30	213,500	-	-	2
WMC122610	24	M24 x 710 mm	850	75	10.0	16.0	30	213,500	-	-	2
WMC122755	30	M24 x 890 mm	995	75	10.0	20.0	30	266,900	-	-	1

\* = Made in UAE.

Hot Dip Galvanized and Stainless Steel option available on request.

The sizes of the Clevis Hangers can be modified to be used with Rubber Support Inserts.

Custom made Clevis Hangers are available on request.

