

# IH126K Phenolic Insulation Block 20 mm Thick

(D 10 10)

for steel, copper and plastic pipe 15 - 168 mm



## Features and Benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.037 W/(mK) at 10 °C
- thermal conductivity determined by testing cylindrical specimen according to BS EN ISO 8497
- reaction to fire: BL-s1 d0
- density: <111mm OD pipe, 60kgs/m<sup>3</sup>
- density: 111mm to 169mm OD pipe, 80kgs/m<sup>3</sup>
- temperature resistance from -50 °C to +110 °C



Part No.	D (mm)	DN	Pack 1
8901020015	15	-	50
8901020021	21 - 22	15	50
8901020027	27 - 28	20	50
8901020034	34 - 35	25	25
8901020042	42	32	25
8911020048	48	40	25
8911020054	54	-	50
8911020060	60	50	50
8911020066	66	-	50
8911020076	76	65	5
8911020089	89	80	15
8911020108	108	-	5
8911020114	114	100	5
8911020133	133	-	3
8911020140	140	125	15
8911220168	168	150	3