

# Pacifyre® S Silicone Fire Sealant

(U 04 95)



## Features and Benefits

- up to EI 240 for linear gap seals
- suitable for linear joints in walls and floors with max. 25% movement
- for sealing annular joints around pipes, fire collars and fire sleeves or wraps
- very good adhesion to most substrates
- easy to apply
- colour-fast, UV-stable and paintable after curing
- remains permanently elastic after curing
- skin formation in approx. 20 min.
- curing rate 1mm/24h
- 16 shore A hardness
- indoor emission level A+
- temperature resistance from -10 °C to +140 °C
- application temperature: +5 °C up to +30 °C
- fire class B1 (DIN 4102-2)
- CE marked
- tested and approved according to EN 1366-4 and EN 1366-3
- for more information, please refer to the Declaration of Performance / ETA, [www.walraven.com/pacifyre](http://www.walraven.com/pacifyre)



Part No.	Colour	Certification	Cont.	Pack 1
2180100020	White	ETA	300 ml	12

### Complementary

Pacifyre® MK II Fire Sleeve (P)  
 Pacifyre® EFC Fire Collar  
 Pacifyre® BFC

### Complementary

Pacifyre® ID-Card  
 Tangit 2C Pistol PP6  
 WIS Dispenser Gun