

# BIS Mengerling® Sealing Ring

for pipe DN 50 - DN 200

(N 20 05)



## Features and benefits

- easy to install (without lubricant)
- for use up to 0.5 bar internal pressure
- for connecting and sealing of cast iron pipe with socket with SML or HT/PE-pipe
- material: EPDM rubber, black
- tested according to DIN 4060

Part No.	DN	Model	Type	Pack 1
730 0 050	50	GA-collar to SML or GA-Pipe	I	100
730 0 070	70	GA-collar to SML or GA-Pipe	I	100
730 0 100	100	GA-collar to SML or GA-Pipe	I	250
730 0 125	125	GA-collar to SML or GA-Pipe	I	20
730 0 150	150	GA-collar to SML or GA-Pipe	I	20
730 0 200	200	GA-collar to SML or GA-Pipe	I	10
730 1 050	50	GA-collar to SML or GA-Pipe	A	100
730 1 070	70	GA-collar to SML or GA-Pipe	A	100
730 1 100	100	GA-collar to SML or GA-Pipe	A	250
730 1 125	125	GA-collar to SML or GA-Pipe	A	20
730 1 150	150	GA-collar to SML or GA-Pipe	A	20
730 1 200	200	GA-collar to SML or GA-Pipe	A	10
730 2 050	50	GA-collar to HT/PE-Pipe	IS	100
730 2 125	125	GA-collar to HT/PE-Pipe	IS	20
730 3 050	50	GA-collar to HT/PE-Pipe	AS	100
730 3 070	70	GA-collar to HT/PE-Pipe	AS	100
730 3 125	125	GA-collar to HT/PE-Pipe	AS	20

*Sealing Rings for HT-tube (Part No. 730 X XXX) DN 40 up to DN 200 on stock.*