

BIS RapidStrut® Cantilever Arm 41x41D (BUP1000)

(H 08 10)

fixing to wall



Features and benefits

- wall plate welded on Strut Profile
- slots at 90° to each other to simplify fixing
- CO₂ welded
- inward formed flanges with serrated profile for extra grip
- material: steel 1.0332
- surface protection:
 - product is part of the BIS UltraProtect® 1000 system
 - suitable for in- and outdoor applications
 - stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- tested for fire safety



Part No.	L	B	H	s1	d1	S	k	From rail	Pack 1
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
6603883	450 mm	45	175	8.0	30 x 13	22	137.5	Strut 41x41Dx2.5	8
6603884	600 mm	45	175	8.0	30 x 13	22	137.5	Strut 41x41Dx2.5	4
6603885	750 mm	45	175	8.0	30 x 13	22	137.5	Strut 41x41Dx2.5	4
6603886	1,000 mm	45	175	8.0	30 x 13	22	137.5	Strut 41x41Dx2.5	1

Strut 82 (41x2) and above tested for fire safety.

For more information about the max. allowed load ($F_{a,2}$) please refer to the loading tables or our online datasheet 'Technical Details BIS RapidStrut®'.

