

# IH105 / IH144 Standard U Bolt

(P 04 35)

for steel, copper and insulated pipes 21 - 324 mm



## Features and benefits

- Type IH105: zinc plated, for steel pipe
- other finishes available on request
- Type IH144: nylon coated, for copper pipe

Part No.	D (mm)	D (")	DN	Type	G	H (mm)	Lm1 (mm)	k (mm)	Pack 1
B7103022	21	1/2	15	IH105	M6	54	30	27	100
B7103023	27	3/4	20	IH105	M6	59	30	33	100
B7103035	34	1	25	IH105	M6	66	30	40	100
B7103042	42	1 1/4	32	IH105	M10	80	40	55	100
B7103049	48	1 1/2	40	IH105	M10	90	40	61	50
B7103061	60	2	50	IH105	M10	100	40	70	50
B7103076	77	2 1/2	65	IH105	M10	117	40	86	50
B7103089	92	3	80	IH105	M12	127	40	102	50
B7103115	116	4	100	IH105	M12	152	40	126	25
B7103140	142	5	125	IH105	M12	182	40	152	25
B7103168	172	6	150	IH105	M12	212	40	182	25
B7103219	220	8	200	IH105	M16	276	40	236	1
B7103273	273	10	250	IH105	M16	333	40	289	1
B7103324	324	12	300	IH105	M20	383	40	344	1

PP-strip is used to isolate copper pipe from any supporting steel structure. Please refer to page Q 05 85. Please specify if required.

