

# IH126K Phenolic Insulation Block 30 mm Thick

(D 10 20)

for steel, copper and plastic pipe 15 - 273 mm



## Features and benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate recommended above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.037 W/(mK) at 10 °C
- thermal conductivity determined by testing cylindrical specimen according to BS EN ISO 8497
- reaction to fire: BL-s1 d0
- density: <111mm OD pipe, 60kgs/m<sup>3</sup>
- density: 111mm to 169mm OD pipe, 80kgs/m<sup>3</sup>
- density: >170mm OD pipe, 120kgs/m<sup>3</sup>
- temperature resistance from -50 °C to +110 °C



Part No.	D (mm)	DN	Pack 1
8901030015	15	-	25
8901030021	21 - 22	15	25
8901030027	27 - 28	20	25
8901030034	34 - 35	25	50
8901030042	42	32	50
8911030048	48	40	5
8911030054	54	-	5
8911030060	60	50	5
8911030066	66	-	5
8911030076	76	65	25
8911030089	89	80	25
8911030108	108	-	5
8911030114	114	100	15
8911030133	133	-	15
8911030140	140	125	5
8911230168	168	150	3
8911230219	219	200	4
8911230273	273	250	2