

# IH126K Phenolic Insulation Block 40 mm Thick

(D 10 25)

for steel, copper and plastic pipe 15 - 273 mm



## Features and benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate recommended above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.037 W/(mK) at 10 °C
- thermal conductivity determined by testing cylindrical specimen according to BS EN ISO 8497
- reaction to fire: BL-s1 d0
- density: <111mm OD pipe, 60kgs/m<sup>3</sup>
- density: 111mm to 169mm OD pipe, 80kgs/m<sup>3</sup>
- density: >170mm OD pipe, 120kgs/m<sup>3</sup>
- temperature resistance from -50 °C to +110 °C



Part No.	D (mm)	DN	Pack 1
8901040015	15	-	50
8901040021	21 - 22	15	50
8901040027	27 - 28	20	50
8901040034	34 - 35	25	25
8901040042	42	32	5
8911040048	48	40	5
8911040054	54	-	25
8911040060	60	50	25
8911040066	66	-	25
8911040076	76	65	5
8911040089	89	80	3
8911040108	108	-	5
8911040114	114	100	3
8911040133	133	-	-
8911040140	140	125	3
8911040159	159	-	5
8911240168	168	150	6
8911240219	219	200	2
8911240273	273	250	2