

# IH126K Phenolic Insulation Block 40 mm Thick

(D 10 25)

for steel, copper and plastic pipe 15 - 273 mm



## Features and benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.032 W/m C at 10 °C
- density: <111mm OD pipe, 60kgs/m<sup>3</sup>
- density: 111mm to 169mm OD pipe, 80kgs/m<sup>3</sup>
- density: >170mm OD pipe, 120kgs/m<sup>3</sup>
- temperature resistance from -50 °C to +110 °C
- Class 'O' to BS476/7
- ignitability BS476 Pt5, Class 'P'
- 5% smoke emission to BS 5111

Part No.	D (mm)	DN	Pack 1
89 0 10 40 015	15	-	1
89 0 10 40 021	21 - 22	15	1
89 0 10 40 027	27 - 28	20	1
89 0 10 40 034	34 - 35	25	1
89 0 10 40 042	42	32	1
89 1 10 40 048	48	40	1
89 1 10 40 054	54	-	1
89 1 10 40 060	60	50	1
89 1 10 40 066	66	-	1
89 1 10 40 076	76	65	1
89 1 10 40 089	89	80	1
89 1 10 40 108	108	-	1
89 1 10 40 114	114	100	1
89 1 10 40 133	133	-	1
89 1 10 40 140	140	125	1
89 1 10 40 159	159	-	1
89 1 12 40 168	168	150	1
89 1 12 40 219	219	200	1
89 1 12 40 273	273	250	1