

# WNP Nail Plug

easy to install hammer-set anchor

(L 07 18)



## Features and benefits

- quick and easy to install
- pre-assembled
- long expansion zone provides stability
- can be adjusted or dismantled
- material: steel
- material: high quality PA6 polyamide
- zinc plated
- substrate type:
  - concrete
  - masonry
  - rock
  - stone
  - sand-lime bricks
  - natural stone

| Part No. | Code      | L      | d <sub>s</sub> | d <sub>0</sub> | h <sub>0</sub> | l <sub>s</sub> | h <sub>nom,mi</sub><br>n | t <sub>fix,max</sub> | Drive | Rec. Tension Load Solid Brick (kN) | Pack 1 | Pack 2 |
|----------|-----------|--------|----------------|----------------|----------------|----------------|--------------------------|----------------------|-------|------------------------------------|--------|--------|
|          |           |        | (mm)           | (mm)           | (mm)           | (mm)           | (mm)                     | (mm)                 |       |                                    |        |        |
| 62232604 | WNP 6x40  | 40 mm  | 4              | 6              | 40             | 40             | 30                       | 10                   | PZ2   | 0.20                               | 200    | 2,400  |
| 62232606 | WNP 6x60  | 60 mm  | 4              | 6              | 40             | 60             | 30                       | 20                   | PZ2   | 0.20                               | 200    | 2,400  |
| 62232806 | WNP 8x60  | 60 mm  | 4              | 8              | 50             | 60             | 40                       | 20                   | PZ2   | 0.45                               | 100    | -      |
| 62232808 | WNP 8x80  | 80 mm  | 4              | 8              | 50             | 80             | 40                       | 40                   | PZ2   | 0.45                               | 100    | -      |
| 62232810 | WNP 8x100 | 100 mm | 4              | 8              | 50             | 100            | 40                       | 60                   | PZ2   | 0.45                               | 100    | -      |

*Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 2.*

