

Walraven Heavy Duty Clamp HD500 (M8/10) (Black)

(B 10 40)

for steel and stainless steel pipes, including fire mains 12 - 65 mm



Features and benefits

- two-part clamp with two locking bolts
- up to and including 5": locking nut is captive, hidden in plastic holder
- can be used with stainless steel pipe; the epoxy powder coating prevents contact corrosion between clamp and pipe
- suitable for fire mains (DIN1988-600)
- with M8/10 connection for higher flexibility
- heavy design
- with 360° CO2 welded connection nut
- bolts secured with anti-loss washer
- material: steel
- surface protection:
 - black (RAL 9005) epoxy powder coating (60 µm)
 - product is part of the Walraven BIS UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

| Part No. | D (mm) | D (") | DN | G | B (mm) | H (mm) | h (mm) | b x s (mm) | cs | F _{a,z} (N) | Pack 1 |
|----------|-----------|----------|----|-------|-----------|-----------|-----------|---------------|----|-------------------------|--------|
| 3303B016 | 12 - 16 | - | - | M8/10 | 71.7 | 43 | 30.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B023 | 19 - 23 | 1/2 | 15 | M8/10 | 78.5 | 50 | 34.0 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B026 | 22 - 26 | - | - | M8/10 | 81.5 | 53 | 35.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B030 | 25 - 30 | 3/4 | 20 | M8/10 | 85 | 57 | 37.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B036 | 31 - 36 | 1 | 25 | M8/10 | 90.5 | 63 | 40.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B042 | 37 - 42 | - | - | M8/10 | 97.6 | 69 | 43.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B052 | 47 - 52 | 1 1/2 | 40 | M8/10 | 108.8 | 79 | 48.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B058 | 53 - 58 | - | - | M8/10 | 114 | 85 | 51.5 | 30 x 2.5 | M8 | 2,100 | 25 |
| 3303B065 | 59 - 65 | 2 | 50 | M8/10 | 120.8 | 92 | 55.0 | 30 x 2.5 | M8 | 2,100 | 25 |

