

# WUP Uni Plug

(L 07 05)

standard universal anchor for all types of substrates



## Features and benefits

- high load capacity
  - can be used with wood screws, chipboard screws and metric bolts
  - suitable for variety of substrates
  - easily slides into holes
  - does not slip past collar in deep holes
  - does not expand prematurely
  - resists rotation in holes
  - Application:
    - shelves
    - wall-mounted cabinets
    - sanitary fixings
    - HVAC and plumbing fixings
  - material: high quality PA6 polyamide
- substrate type:
    - lightweight concrete
    - concrete
    - masonry
    - hollow masonry
    - rock
    - sand-lime bricks
    - natural stone
    - gypsum

Part No.	Code	d <sub>0</sub>	h <sub>0</sub>	d <sub>s,w</sub>	d <sub>s,m</sub>	l <sub>s,min</sub>	Rec. Load Brick	Rec. Load Perforated Brick	Rec. Load C20/25 Concrete	Rec. Load Lightweight Concrete		Pack 1	Pack 2
		(mm)	(mm)	(mm)	(mm)	(mm)	(kN)	(kN)	(kN)	(kN)	(kN)		
610 0 708	WUP 8x40	8	50	4.5 - 6.0	M5	44	1.00	0.40	1.15	0.19	1.00	100	3,600

*Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 5.*

