

Walraven Pacifyre[®] Wool Coating

(U 04 115)



Avantages et caractéristiques

- offers protection up to EI 120
 - Coating or filler designed for fire protection in cables and penetration seals
 - Particularly suitable for applications requiring thin dry film thicknesses
 - Forms a ceramifying protective layer when exposed to fire due to the Strong Endothermic Reaction
 - Suitable for protective cable coating, cable and pipe penetration sealing, and large-surface bonding on critical substrates
 - Can be applied indoors and in sheltered outdoor areas
 - Withstands humidity, freeze-thaw cycles, UV radiation, and various oils and chemicals
 - Offers strong mechanical resistance
 - viscosity can be tailored to specific needs
 - coating can be applied using a brush, paint roller, or airless spraying machine
- Solvent-free and halogen-free
 - tested and approved according to EN 1366-3



| N°Art. | L | B (mm) | H (mm) | Couleur | Vol. | Cond.1 |
|------------|--------|-----------|-----------|---------|---------|--------|
| 2139400003 | 240 mm | 240 | 50 | Blanc | 310 ml | 12 |
| 2139400005 | 227 mm | 227 | 180 | Blanc | 5 kg | 1 |
| 2139400001 | 344 mm | 344 | 218 | Blanc | 12,5 kg | 1 |