

BIS Mengering[®] Kombi

za cijevi DN 50 - DN 300

(N 10 10)



Prednosti i osobine

- sigurnosna oklopna manžetna za cijevi
- univerzalna za sve spojnice sa jednim ili dva vijka za zatvaranje (npr. BIS Mengering[®] Max ili CV)
- šestokutni inbus vijci za zatvaranje sa sigurnosnim prstenom (do DN 200)
- preko dimenzije DN 200 sa šestokutnim vijcima
- materijal: čelik
- elektrizom cinkovan

Art.br.	DN	Model	B (mm)	b (mm)	S (mm)	T _(max.) (Nm)	Za	KK
7440050	50	2-dijela	124	72	51	23,0 - 25,0	< 10 bar	10
7440070	70	2-dijela	144	72	51	23,0 - 25,0	< 10 bar	10
7440080	75 / 80	2-dijela	149	72	51	25,0 - 28,0	< 10 bar	10
7440100	100	2-dijela	184	87	56	35,0 - 40,0	< 10 bar	10
7440125	125	2-dijela	201	98	68	40,0 - 45,0	< 5 bar	10
7440150	150	2-dijela	227	98	68	45,0 - 60,0	< 5 bar	10
7440200	200	3-dijela	275	111	82	50,0 - 65,0	< 3 bar	10
7440250	250	3-dijela	325	111	82	50,0 - 65,0	< 1 bar	1
7440300	300	3-dijela	375	111	82	50,0 - 65,0	< 1 bar	1

T = pritezni moment.

