

BIS Mengering® Rapid

za cijevi DN 40 - DN 200

(N 05 20)



Prednosti i osobine

- jednodijelna spojnica sa jednim vijkom za spajanje
- definitivni profil se dobija u formi alata
- zadovoljava vatrootporne propise
- axialna postojanost momenta do 0,5 bari za dimenzije cijevi DN 40 - DN 200
- jednostavno i lako instaliranje sa vizuelnom kontrolom momenta
- materijal:
 - spojnica: hromirani čelik 1.4510/11 (AISI 430 Ti)
 - elementi za spajanje: čelik 1.4301 / 1.4510/11 (AISI 430 Ti)
 - vijak / navojnica: čelik, cinkovan
 - dihtung od EPDM-gume, crne boje



Art.br.	D (mm)	DN	Vijka	B (mm)	b (mm)	T _(max.) (Nm)	CE	KK
7454050	70	50	M8	80	40	Tight-locking	CE	100
7454070	90	70	M8	100	40	Tight-locking	CE	100
7454080	95	80	M8	105	40	Tight-locking	CE	100
7454100	125	100	M8	135	46	Tight-locking	CE	100
7454125	147	125	M8	162	55	Tight-locking	CE	70
7454150	172	150	M8	187	55	Tight-locking	CE	50
7454200	227	200	M10	244	70	Tight-locking	CE	15

Please note! BIS Mengering® Rapid is alternative for BIS Mengering® CV.

