


BISOFIX[®] PIR20 + HD500

(D 03 56)

za rashladne medije 76,1 - 273,1 mm



Prednosti i osobine

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- ne sadrži FCKW, HFCKW, formaldehid ili kadmium supstance
- otpornost na požar klasa: B2
- PIR density for D <110mm = 80kg/m³
- PIR density for D >110mm = 120kg/m³
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- zaštita materijala:
 - proizvod je deo Walraven BIS UltraProtect[®] sistema
 - pogodan za unutrašnju i spoljašnju upotrebu
 - izdržava min. 1 000 sati sonog sprej testa (max. 5% crvene rdje) prema ISO standardu 9227
- temperature range -45 °C - +105 °C

Art.br.	Consists Of	D (mm)	Model	F _{a,z} (N)	KK
I203304076	I200000076 + 33048116	76,1	BISOFIX [®] PIR20 + HD500 Clamp	390	25
I203304089	I200000089 + 33048133	88,9	BISOFIX [®] PIR20 + HD500 Clamp	430	25
I203304102	I200000102 + 33048140	101,6	BISOFIX [®] PIR20 + HD500 Clamp	450	25
I203304108	I200000108 + 33048154	108,0	BISOFIX [®] PIR20 + HD500 Clamp	500	15
I203304114	I200000114 + 33048154	114,3	BISOFIX [®] PIR20 + HD500 Clamp	1.110	15
I203304133	I200000133 + 33048183	133,0	BISOFIX [®] PIR20 + HD500 Clamp	1.360	5
I203304140	I200000140 + 33048183	139,7	BISOFIX [®] PIR20 + HD500 Clamp	1.410	5
I203304160	I200000160 + 33048202	159,0 - 160,0	BISOFIX [®] PIR20 + HD500 Clamp	1.520	5
I203304168	I200000168 + 33048219	168,3	BISOFIX [®] PIR20 + HD500 Clamp	1.570	5
I203304219	I200000219 + 33068264	219,1	BISOFIX [®] PIR20 + HD500 Clamp	1.620	2
I203304273	I200000273 + 33068325	273,1	BISOFIX [®] PIR20 + HD500 Clamp	1.670	2