

WIS Chemical Anchor WVSF200


(L 03 90)

high performance chemical anchoring system for cracked concrete and rebar connections



Prednosti i osobine

- reduced edge and anchor spacing distances
 - always correct mixing ratio thanks to the static mixer nozzle
 - approved for use with rebars as anchors in non-cracked concrete
 - cartridge may be used up over several times (each installation after a break requires new mixing nozzle)
 - ETA Option 1 approval for cracked and non-cracked concrete
 - A+ VOC emissions class
 - ETA TRO23 for post-installed rebar connections
 - seismic performance category C1 for design of anchorages under seismic action
 - tested according to LEED 2009 EQ c4.1, SCAQMD rule 1168 (2005)
 - WRAS Material Approval for contact with potable water
- substrate type:
 - cracked concrete
 - non-cracked concrete



Art.br.	Kode	ETA	LEED	WRAS	VOC+	Seismic	Sadr.	KK
6099123	WVSF200	ETA	LEED	WRAS	VOC+	C1	300 ml	12

For more information, please refer to the ETA report.

Kompetabilno

WIS Extension Pipe
WIS Brush
WIS Blow Pump

Kompetabilno

WIS Dispenser Gun
WIS Plastic Mesh Sleeve
WIS Threaded Rod