

WUP Uni Plug

standard universal anchor for all types of substrates

(L 07 05)



Prednosti i osobine

- high load capacity
 - can be used with wood screws, chipboard screws and metric bolts
 - suitable for variety of substrates
 - easily slides into holes
 - collar prevents the plug from sliding into deeper holes
 - does not expand prematurely
 - resists rotation in holes
 - Application:
 - shelves
 - wall-mounted cabinets
 - sanitary fixings
 - HVAC and plumbing fixings
 - material: high quality PA6 plyamide
- substrate type:
 - lightweight concrete
 - concrete
 - masonry
 - hollow masonry
 - rock
 - sand-lime bricks
 - natural stone
 - gypsum

Art.br.	Kod e	L	d ₀	h ₀	d _{s,w}	d _{s,m}	l _{s,min}	Rec. Load Brick	Rec. Load Perforated Brick	Rec. Load C20/25 Concrete	Rec. Load Lightweight Concrete	Rec. Load Sandstone	KK	VP
			(mm)	(mm)	(mm)	(mm)	(mm)	(kN)	(kN)	(kN)	(kN)	(kN)		
6100706	WUP 6x30	30 mm	6	40	3,5 - 5,0	M4	34		0,20	0,45	0,12	0,70	100	3.600
6100708	WUP 8x40	40 mm	8	50	4,5 - 6,0	-	44	1,00	0,40	1,15	0,19	1,00	100	3.600
6100710	WUP 10x50	50 mm	10	70	6,0 - 8,0	-	54	1,10	0,45	1,90	0,30	1,80	50	1.800
6100712	WUP 12x60	60 mm	12	70	8,0 - 10,0	-	64	1,50	0,50	2,70	0,40	2,10	25	900

Given recommended tension loads have been reached using a maximum diameter wood screw and include a safety factor of 5.

