

Walraven VibraTek® MS-2X Spring Mount

(L2 05 12)

high performance spring isolator for medium to heavy machinery



Prednosti i osobine

- recommended for equipment with low working speeds, from 600 rpm and above
- epoxy powder-coated base, caps and springs provide increased resistance to corrosion
- flexible internal filler prevents debris and solid elements entering and damaging the spring under load
- ribs in the metal base provide increased stiffness
- slot holes facilitate positioning and anchoring to the base material
- Technical Data
 - ratio $K_x / K_z = 0.98$
 - ratio $K_y / K_z = 1.4$
- working temperature range -90 °C till 150 °C

Art.br.	G	L	B	H	d1	d2	Min. Load (N)	Max. Load (N)	Min. Optimal Load (N)	Max. Optimal Load (N)	Max. Deflection (mm)	KK
2802003000	M12	83 mm	210	122	11	20	300	3.000	600	2.760	25,0	5
2802004000	M12	83 mm	210	122	11	20	400	4.000	800	3.680	25,0	5
2802006000	M12	83 mm	210	122	11	20	600	6.000	1.200	5.520	25,0	5
2802008000	M12	83 mm	210	122	11	20	800	8.000	1.600	7.360	25,0	5
2802010000	M12	83 mm	210	122	11	20	1.000	10.000	2.000	9.200	25,0	5
2802012000	M12	83 mm	210	122	11	20	1.200	12.000	2.400	11.040	25,0	5

See Product Data Sheet for further technical information.

