

Walraven VibraTek® MS-4 Spring Mount

(L2 05 15)

high performance spring isolator for heavy machinery



Prednosti i osobine

- recommended for equipment with low working speeds, from 600 rpm and above
- epoxy powder-coated base, caps and springs provide increased resistance to corrosion
- flexible internal filler prevents debris and solid elements entering and damaging the spring under load
- ribs in the metal base provide increased stiffness
- slot holes facilitate positioning and anchoring to the base material
- Technical Data
 - average ratio $K_x / K_z = K_y / K_z = 2.0$
- working temperature range -90 °C till 150 °C

Art.br.	G	L	B	b3	H	Min. Load (N)	Max. Load (N)	Min. Optimal Load (N)	Max. Optimal Load (N)	Max. Deflection (mm)	KK
2800501000	M10	145 mm	158	140	80	100	1.000	200	900	23,0	5
2800501500	M10	145 mm	158	140	80	130	1.500	260	1.350	23,0	5
2800502000	M10	145 mm	158	140	80	200	2.000	400	1.800	23,0	5
2800503000	M10	145 mm	158	140	80	300	3.000	700	2.700	23,0	5
2800504000	M10	145 mm	158	140	80	400	4.000	800	3.600	23,0	5
2800505000	M10	145 mm	158	140	80	500	5.000	1.000	4.500	23,0	5

See Product Data Sheet for further technical information.

